



P.C.: 790100601

Maya V SAE 5W40

Full Synthetic Engine Oil SM

This product is a high quality full synthetic long-life engine oil that is recommended for all petrol engines with or without catalytic converter. It can also be used in diesel engines, turbocharged or naturally aspirated cars and light vans. This product is designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and better low-temperature performance over the life of the oil. This product has the API SM specification but can also be used where older API specifications are applicable like SJ and SL.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA A3 / B3-16	MB 229.3
ACEA A3 / B4	OPEL GM-LL-A-025
API CF	OPEL GM-LL-B-025
API SM	PORSCHE A40
BMW LONGLIFE-01	PSA B71 2296
FIAT 9.55535-H2	RENAULT RN 0700
FIAT 9.55535-M2	RENAULT RN 0710
FIAT 9.55535-Z2	VW 502.00
MB 226.5	VW 505.00

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,856
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	86,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,4
Viscosity Index	ASTM D2270		175
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,6
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,20

All data on this technical data sheet is indicative only

V 202404.01