



P.C.: 790100701

Gamma P SAE 10W40

Semi-Synthetic Engine Oil SM

This product is a high quality semi-synthetic long-life engine oil. This product can be used for the lubrication of all 4-Stroke gasoline and diesel engines, which makes it perfect oil for the whole fleet. It is also suitable for vehicles that operate with a direct fuel injection. The total engine protection of this lubricant ensures outstanding engine cleanliness and it is very suitable for cold starts and Start-Stop traffic. This product has the API SM specification but can also be used where older API specifications are applicable like SJ and SL.



BASE OIL:
SEMI-SYNTHETIC

SPECIFICATIONS

ACEA A3 / B3-16	MB 229.3
ACEA A3 / B4	MB 229.3
API SM	PSA B71 2300-2022
FIAT 9.55535-D2	RENAULT RN 0700
FIAT 9.55535-G2	RENAULT RN 0710
LADA LADA-AVTOVAZ	VW 501.01
MB 226.5	VW 505.00
MB 229.1	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,868
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	95,4
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,1
Viscosity Index	ASTM D2270		152
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,00

All data on this technical data sheet is indicative only

V 202404.01