



P.C.: 790101001

Vura U SAE 15W40

Multi Grade Engine Oil SL/CF

This engine oil is made of mineral base oils. It contains of extremely well formulated additive packages. It is suitable for gasoline and diesel vehicles that are in need of the API SL specification or older. This oil can be used for direct injection such as Common Rail, HDI, CDI, etc. Also this oil can be used in supercharged vehicles. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications.



BASE OIL:
MINERAL

SPECIFICATIONS

ACEA A3 / B3-16

PSA B71 2295

ACEA A3 / B4

RENAULT RN 0700

API SL / CF

RENAULT RN 0710

FIAT 9.55535-D2

VW 501.01

FIAT 9.55535-G2

VW 505.00

MB 229.1

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,885
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	103,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,7
Viscosity Index	ASTM D2270		130
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	1,03

All data on this technical data sheet is indicative only

V 202404.01