



Vura X SAE 20W50

Multi Grade Engine Oil SL/CF

This engine oil is made of mineral base oils. It contains of extremely well formulated additive packages. It is suitable for gasoline and diesel vehicles that are in need of the API SL specification or older. This oil is also particularly suitable for four-cylinder and turbo diesel engines with or without turbo. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications. One of the reasons why this product is extremely suitable for also the more modern car portfolio is its engine cleanliness properties and its additive package that ensures extended oil drain intervals and fuel saving.



BASE OIL:
MINERAL

SPECIFICATIONS

ACEA A3 / B3-16

PSA B71 2295

ACEA A3 / B4

VW 501.01

API SL / CF

VW 505.00

MB 229.1

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,890
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	155,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	18,0
Viscosity Index	ASTM D2270		125
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-24
Flash point	ASTM D92	°C	235
Sulphated ash content	ASTM D874	%	1,03