



P.C.: 790101701

Alpha G SAE 5W40

Full Synthetic Engine Oil SN/CF

This product is a very advanced full synthetic engine oil that has been developed for gasoline and diesel engines. The full synthetic technology in this engine oil is several times more able to effectively remove sludge and dirt from engines than a mineral oil. This product meets and exceeds many of the industry and OEM specifications required by newer modern gasoline and diesel powered automobile engines. This product has active cleaning agents that help to reduce the deposit and sludge build up in the engine. This product can be recommended for all types of modern vehicles including vehicles with turbochargers, superchargers and multi-valve injected engines.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA A3 / B3-16	MB 229.3
ACEA A3 / B4	OPEL GM-LL-A-025
API CF	OPEL GM-LL-B-025
API SN	PORSCHE A40
BMW LONGLIFE-01	PSA B71 2296
FIAT 9.55535-H2	RENAULT RN 0700
FIAT 9.55535-M2	RENAULT RN 0710
FIAT 9.55535-Z2	VW 502.00
MB 226.5	VW 505.00

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,858
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	86,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,4
Viscosity Index	ASTM D2270		175
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,5
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,27

All data on this technical data sheet is indicative only

V 202404.01