

PC: 790101901



Alpha R SAE 10W60

Semi-Synthetic Engine Oil SN/CF

This product is a very advanced semi-synthetic engine oil. This product is suitable in four-stroke petrol and diesel engines for passenger cars, and light vans. It can be used in direct-injection diesel engines such as common rail, HDI, CDI etc. This product is formulated with a good all year round additive package and can be used in a wide variety of vehicles. One of the added values to this 10W60 grades compared to other grades is that it is particularly suitable in extreme operating conditions. It ensures a flexible combination of high and low temperature protection.



BASE OIL:

SEMI-SYNTHETIC

SPECIFICATIONS

ACEA A3 / B4 VW 501.01

API SN / CF VW 505.00

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|----------|-------|
| Density | ASTM D4052 | kg/l | 0,866 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm²/s | 171,0 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm²/s | 24,5 |
| Viscosity Index | ASTM D2270 | | 175 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 9,6 |
| Pour point | ASTM D6892 | °C | -36 |
| Flash point | ASTM D92 | °C | 238 |
| Sulphated ash content | ASTM D874 | % | 1,10 |

All data on this technical data sheet is indicative only