



Alpha Z SAE 20W50

Multi Grade Engine Oil SN/CF

This product is a very advanced mineral engine oil that has been developed for gasoline and diesel engines. This product is made of the finest European base oils and additives. This product meets and exceeds many of the industry and OEM specifications required by newer modern gasoline and diesel powered automobile engines. This product has active cleaning agents that help to reduce the deposit and sludge build up in the engine. This product can be recommended for all types of modern vehicles including vehicles with turbochargers, superchargers and multi-valve injected engines.



BASE OIL:
MINERAL

SPECIFICATIONS

ACEA A3 / B3-16

PSA B71 2295

ACEA A3 / B4

VW 501.01

API SN / CF

VW 505.00

MB 229.1

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,892
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	167,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	18,3
Viscosity Index	ASTM D2270		122
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,5
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	222
Sulphated ash content	ASTM D874	%	1,03