



PC: 790102201

Zeta C SAE 0W20

Fuel Economy Engine Oil GF-5

Today's engines are smaller, more efficient, more advanced and more powerful. Because of this, these engines need to operate in more extreme conditions. If not good protected by good oil, the cylinder walls, pistons, piston rings, connecting rods and spark plugs can cause permanent damage. This product has been formulated with sophisticated European base oils and additives that prevent this from happening. This is a full synthetic engine oil that we have specifically formulated for consumers that would like to experience an extreme high level of fuel economy in their gasoline passenger car, SUV, van or light truck. This all year round oil is developed in order to meet the challenging requirements of fuel efficient combustion vehicles as well as hybrid vehicles where CO2 reduction is very important. Also this product its very low viscosity ensures that it significantly reduces wear, soot ad deposits and keeps the engine clean.

| ZETA C SAE OW/20 |
|--|
| Auto or a large Auto or a large Material and a large |

BASE OIL: FULL SYNTHETIC

SPECIFICATIONS

| ACURA - | FIAT 9.55535-GSX |
|------------------|-------------------|
| API SN PLUS | FORD WSS-M2C945-A |
| API SN / RC | FORD WSS-M2C946-A |
| API SP | FORD WSS-M2C947-A |
| API SP / RC | FORD WSS-M2C962-A |
| BUICK - | GM DEXOSI™ GEN 3 |
| CADILLAC - | GMC - |
| CHEVROLET - | ILSAC GF-5 |
| CHRYSLER MS 6395 | ILSAC GF-6 A |
| DODGE - | JEEP . |
| FIAT 9.55535-CR1 | |

| GRADE | METHOD | UNIT | VALUE |
|------------------------------|------------|----------|-------|
| Density | ASTM D4052 | kg/l | 0,849 |
| Kinematic viscosity @ 40 °C | ASTM D445 | mm²/s | 45,6 |
| Kinematic viscosity @ 100 °C | ASTM D445 | mm²/s | 8,7 |
| Viscosity Index | ASTM D2270 | | 173 |
| B.N. (HCL04 method) | ASTM D2896 | mg KOH/g | 8,1 |
| Pour point | ASTM D6892 | °C | -48 |
| Flash point | ASTM D92 | °C | 222 |
| Sulphated ash content | ASTM D874 | % | 0,88 |

All data on this technical data sheet is indicative only

V 202404.01

Maxmo Lubricants B.V.

```
PRECISION
```