



P.C.: 790102801

## Zeta O SAE 0W30

Fuel Economy Engine Oil

This full synthetic engine oil is formulated for the VW group. This product can be used in petrol and diesel engines. These oils are especially for Petrol "Pumpe-Duse" (unit injector or PD engines) engines running on extended service intervals (30.000 – 50.000 km / 24 months). They are also particularly suitable for diesel engines with extended service intervals of up to 50.000 km / 2 years. They cannot be used for engines with a single injector pump. This engine oil has very high fuel saving properties. This oil should not be used in engines where the VW 503.01 is required.



BASE OIL:  
FULL SYNTHETIC

### SPECIFICATIONS

ACEA A5 / B5

BMW LONGLIFE-01 FE

API SN / CF

VOLVO VCC 95200377

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,857
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	53,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	9,6
Viscosity Index	ASTM D2270		168
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,2
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	226
Sulphated ash content	ASTM D874	%	1,28

All data on this technical data sheet is indicative only

V 202404.01