



## Zeta J SAE 5W30

### Fuel Economy Engine Oil

This is a full synthetic engine oil that has been developed for the FORD group that have the Ford WSS-M2C-913-A/B specification and replaces the M2C-913-A/B specifications. This specification is mandatory for all FORD models from model year 2009 and higher. Also this product is needed when the vehicles are equipped with the 2,2 Duratorq engines. This engine oil has over 3% fuel saving properties and can also be used for vehicles that have older specifications with the exception of the models which are equipped with pump injectors (Galaxy I en II) and Ford Ka (diesel and gasoline from 2009).



BASE OIL:  
**FULL SYNTHETIC**

#### SPECIFICATIONS

ACEA A1 / B1-12

FORD WSS-M2C913-C / D

ACEA A5 / B5

ILSAC GF-5

API CF

JAGUAR-LAND ROVER

API SL

STJLR.03.5003

FIAT 9.55535-G1

RENAULT RN 0700

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,852
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	55,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	10,0
Viscosity Index	ASTM D2270		170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	210
Sulphated ash content	ASTM D874	%	1,09