



P.C.: 790103001

Sigma X C2 SAE 5W30

MID SAPS Engine Oil C2

This product meets all requirements of the ACEA C2. This means that this engine oil is intended for use as catalyst compatible oil at extended drain intervals in vehicles with all types of modern aftertreatment systems and high performance passenger cars, light duty van gasoline and diesel engines that are designed to be capable of using low viscosity oils with a minimum HTHS viscosity of 2.9 mPa*s.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA C2

API SN / CF

FIAT 9.55535-S1

ILSAC GF-5

PSA B71 2290-2014

RENAULT RN 0700

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,856
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	57,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	10,1
Viscosity Index	ASTM D2270		167
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,5
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	232
Sulphated ash content	ASTM D874	%	0,79

All data on this technical data sheet is indicative only

V 202404.01