



Sigma M C5 SAE 0W20

LOW SAPS Engine Oils

This is a full synthetic engine oil that has been developed for the newest Mercedes Benz vehicles, Jaguar vehicles and Land Rovers. The ultra low viscosity ensures optimal fuel efficiency properties. This product contains of the MB 229.71 specification, ensuring that this oil works particularly well in the latest Mercedes Benz E-Class engines, including the 2017 E 220d 4MATIC All-Terrain 213.217 and the 2017 d 4MATIC Coupe 238.315. This product is also very suitable for the use in a variety of Land Rovers and Jaguar XE, XK and F. This product has outstanding fluidity with cold start properties, can be used perfectly in city traffic and long distance driving, and ensures high levels of fuel saving.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA C5	HONDA -
ACEA C6	HYUNDAI .
ACURA -	ILSAC GF-5
API SN PLUS	ILSAC GF-6 A
API SN / RC	INFINITI -
API SP	JAGUAR-LAND ROVER
API SP / RC	STJLR.03.5006
ASTON MARTIN .	JAGUAR-LAND ROVER STJLR.51.5122
BMW LONGLIFE-14FE+	JEEP .
BMW LONGLIFE-17FE+	KIA .
BUICK -	LEXUS -
CADILLAC -	LINCOLN -
CHEVROLET -	MAZDA -
CHRYSLER MS 12145	MB 229.71
CHRYSLER MS 6395	MB 229.72
DODGE -	MG -
FIAT 9.55535-CR1	MINI .
FIAT 9.55535-DM1	NISSAN .
FIAT 9.55535-DSX	OPEL OV 040 1547 - A20
FIAT 9.55535-GSX	PERODUA -
FORD WSS-M2C945-A	ROEWE -
FORD WSS-M2C945-B1	SCION -
FORD WSS-M2C946-A	SUBARU .
FORD WSS-M2C946-B1	SUZUKI .
FORD WSS-M2C947-A	TATA -
FORD WSS-M2C947-B1	TIANJIN -
FORD WSS-M2C962-A1	TOYOTA .
GM DEXOSD™	VOLVO VCC RBS0-2AE
GMC -	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,842
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	39,3
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	8,3
Viscosity Index	ASTM D2270		192
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,8
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	0,79