



P.C.: 790104101

Kappa L C4 SAE 5W30

LOW SAPS Engine Oil C4

This C4 engine oil is a high quality full synthetic lubricant for the use in gasoline and diesel engines for passenger cars, vans and light duty vehicles. This lubricant is based on the most advanced low SAPS technology with a minimum HTHS viscosity of 3.5 mPa.s. Meaning that this product can be particularly useful when low sulphated ash, phosphor and sulphur contents are required. It enhances the lifetime of the DPF and the TWC, and maintains the high fuel economy rating of the engine. It is suitable for use in any Renault requiring RN0720 specification, but also Nissan or other OEM requiring an ACEA C4 type of oil.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA C3	MB 229.51
ACEA C4	NISSAN .
FIAT 9.55535-S4	RENAULT RN 0720
MB 226.51	RENAULT RN 0720
MB 226.51	SUZUKI .
MB 229.31	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,854
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	68,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	11,7
Viscosity Index	ASTM D2270		169
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,2
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	0,50

All data on this technical data sheet is indicative only

V 202404.01