



## Omega X PAO SAE 5W30

### PAO Technology Engine Oil

This is a full synthetic engine oil that is formulated with our PAO (Poly Alpha Olefin) technology. This product is suitable for passenger cars equipped with gasoline, diesel and LPG engines and that have after treatment devices and diesel particle filters. The PAO base oils used in this formulation ensure excellent low temperature fluidity, oxidation stability and thermal stability. The PAO synthetic base stocks offer low volatility required to perform the harshest temperatures. This product has exceptional properties compared to normal full synthetic engine oils and meets a variety of specifications. This product can be used perfectly in applications that are in need of demanding properties like racing and sporty driving.



BASE OIL:  
**FULL SYNTHETIC**

#### SPECIFICATIONS

ACEA C2	MB 229.51
ACEA C3	MB 229.52
API SN PLUS	OPEL GM-LL-A-025
API SP	OPEL GM-LL-B-025
BMW LONGLIFE-04	OPEL OV 040 1547 - D30
FIAT 9.55535-S3	OPEL OV 040 1547 - G30
GM DEXOS1™ GEN 2	PORSCHE C30
GM DEXOS2™	VW 503.01
MB 229.31	VW 504.00 / 507.00

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,853
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	70,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	11,6
Viscosity Index	ASTM D2270		161
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	230
Sulphated ash content	ASTM D874	%	0,70