



P.C.: 790105301

Maya C SAE 0W30

Full Synthetic Engine Oil SM

This is a full synthetic engine oil that offers excellent fluidity at low temperatures. A result of this is that this product can be used perfectly in engines that have start-stop mechanisms or vehicles that are used for short-distance driving. This product can be used in all 4-stroke engines, four-valve, turbocharges, and 4-stroke diesel engines with or without turbo. Please note that this product is not suitable in vehicles that have diesel particle filters.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA A3 / B4

RENAULT RN 0700

API SN / CF

RENAULT RN 0710

BMW LONGLIFE-01

VW 502.00

MB 229.3

VW 505.00

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,844
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	66,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	11,9
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,1
Pour point	ASTM D6892	°C	-51
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,10

All data on this technical data sheet is indicative only

V 202404.01