



Beta LCV C3 SAE 5W40

Light Commercial Vehicle Engine Oil

This is a full synthetic engine oil for light commercial vehicles, that uses the latest MID SAPS technology. This results into the fact that this product has outstanding fuel economy properties and extended service life. This product can be used in gasoline as well as diesel engines and is suitable for vehicles that have diesel particle filters (DPF) and after treatment devices (ATD). It has all the properties that meet the Dexos 2™ specifications. Hereby it is required for all new GM/Opel/Vauxhall/Chevrolet diesel and gasoline engines. This product can also be used when an older specification (GM-LL-A-025 or GM-B-LL-025) is prescribed. It meets the latest EURO 4 and EURO 5 emission norms and also includes all the specifications of C2 and C3 oil.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA C3	MB 229.31
API CF	MB 229.51
API SN	PORSCHE A40
BMW LONGLIFE-04	RENAULT RN 0700
FIAT 9.55535-GH2	RENAULT RN 0710
FIAT 9.55535-S2	VW 505.01
FORD WSS-M2C917-A	VW 502.00
GM DEXOS2™	VW 505.00
MB 226.5	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,851
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	84,7
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,9
Viscosity Index	ASTM D2270		170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,5
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	235
Sulphated ash content	ASTM D874	%	0,80