



P.C.: 790105901

## Beta LCV SL SAE 10W40

Light Commercial Vehicle Engine Oil

This engine oil is made of semi-synthetic base oils. It contains of extremely well formulated additive packages. This oil is specifically formulated for LCV vehicles. This product can be used in vehicles where the EURO 4 norm is needed. It is suitable for gasoline and diesel vehicles that need the API SL specification or older. This oil can be used for direct injection such as Common Rail, HDI, CDI, etc. Also, this oil can be used in supercharged vehicles. This product has a very high resistance against oxidation, ensures engine protection and meets a variety of specifications.

BASE OIL:  
**SEMI-SYNTHETIC**

## SPECIFICATIONS

**ACEA A3 / B3-16****MB 229.1****ACEA A3 / B4****VW 501.01****API SL / CF****VW 505.00**

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,866
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	91,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	13,8
Viscosity Index	ASTM D2270		155
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	1,00

All data on this technical data sheet is indicative only

V 202404.01