



P.C.: 790107101

Upsilon SP/GF6 SAE 0W40

Full Synthetic Engine Oil SP

Maxmo Lubricants introduces its advanced synthetic engine oil, compliant with the contemporary API SP standards. With its SAE 0W-40 viscosity grade, engines achieve peak fuel efficiency. Our formulation ensures superior protection against wear and maintains pristine engine conditions. Tailored for the latest turbocharged gasoline and diesel cars and light-duty vehicles, it's adeptly crafted for modern Turbocharged Gasoline Direct Injection (TGDI) engines, addressing LSPI (Low Speed Pre Ignition) challenges. Benefit from smooth cold starts due to its remarkable low-temperature fluidity, enjoy reduced fuel consumption and CO2 emissions, and trust in its comprehensive engine protection for both cleanliness and longevity.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA A3 / B4

RENAULT RN 0700

API SP

RENAULT RN 0710

BMW LONGLIFE-01

VW 502.00

MB 229.5

VW 505.00

PORSCHE A40

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,845
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	61,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	12,7
Viscosity Index	ASTM D2270		210
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	12,5
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	222
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01