



Upsilon SP/GF6 SAE 5W40

Full Synthetic Engine Oil SP

Maxmo Lubricants offers a premium synthetic lubricant, crafted from select high-grade base oils and cutting-edge additives, aligning with the contemporary API SP industry benchmark. It ensures minimal resistance during start-up and boasts superior thermal resilience. Our engine oil provides top-tier wear defense and maintains engine purity. Formulated for the latest turbocharged gasoline and diesel cars and light-duty vehicles, it's adeptly tailored for modern Turbocharged Gasoline Direct Injection (TGDI) engines, addressing LSPI (Low Speed Pre Ignition) concerns. Experience comprehensive engine safeguarding with enhanced cleanliness, smooth cold starts due to its exceptional low-temperature fluidity, and benefit from extended oil drain intervals.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA A3 / B4

PSA B71 2296

API SP

RENAULT RN 0700

BMW LONGLIFE-01

RENAULT RN 0710

MB 229.5

VW 502.00

PORSCHE A40

VW 505.00

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,851
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	78,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,0
Viscosity Index	ASTM D2270		168
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	12,5
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	-