



Tau GAS SAE 5W40

LPG, CNG and Dual Fuel powered Gas Engine Oil

Maxmo Lubricants offers an elite synthetic lubricant, formulated from top-tier base oils and the newest generation additives. Tailored for LPG, CNG, and Dual Fuel passenger vehicles, it addresses the elevated combustion temperatures inherent to gas engines, utilizing innovative technology to safeguard valves and counteract acidic byproducts. Our oil is optimized for passenger vehicles with gas engines fueled by LPG, CNG, and Dual Fuel. Its premium nature supports longer drain intervals, aligning with manufacturer directives. With Maxmo, engines benefit from unparalleled protection, ensuring cleanliness, longevity, and smooth cold starts due to its superior low-temperature fluidity.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA C3	MB 229.51
API SN / CF	VW 502.00
FIAT 9.55535-T2	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	81,1
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	10,0
Viscosity Index	ASTM D2270		172
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,0
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	222
Sulphated ash content	ASTM D874	%	-