



P.C.: 790107501

Sigma U C3 PFR SAE 0W30

MID SAPS Engine Oil C3

Maxmo Lubricants presents a premium synthetic lubricant, crafted from elite base oils, meticulously tailored to align with the stringent VW 504.00 and 507.00 specifications, as well as the Long Life III standards of the VAG Group. As a Mid SAPS oil, it's compliant with Euro 4, 5, and 6 standards, ensuring optimal Diesel Particulate Filter protection. This specific viscosity grade has demonstrated superior fuel efficiency compared to the 5W30 grade. It's backward compatible, with 504.00 and 507.00 surpassing all preceding VW specifications. Ideal for all VAG Group vehicles (Volkswagen, Audi, Seat, Skoda) from 2007 onwards with extended oil drain intervals. However, it's not advised for pre-2007 V10 TDI and 5-cylinder 2.5 TDI engines requiring the 506.01 specification, and first-generation engines with pump injector units should opt for the 505.01 specification. With Maxmo, benefit from comprehensive after-treatment system protection, unmatched engine cleanliness and longevity, and reduced fuel consumption and CO2 emissions.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA C2	FIAT 9.55535-S3
ACEA C3	MB 229.1
API SN	MB 229.51
BMW LONGLIFE-04	PORSCHE C30
FIAT 9.55535-DS1	VW 504.00 / 507.00
FIAT 9.55535-GS1	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,842
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	59,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	11,7
Viscosity Index	ASTM D2270		197
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8,3
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	-
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01