



## Sigma U C3 PFR SAE 0W40

LOW SAPS Engine Oil C3

This is a full synthetic engine oil based on carefully selected very high-quality base oils of the latest generation. It offers an excellent fluidity at low temperature, which ensures instant lubrication after starting and will bring wear to a minimum. It is suitable for hybrid cars when the OEM specifications are met. This engine oil is aimed and specifically formulated for usage in gasoline and diesel passenger vehicles equipped with aftertreatment systems. It can be used in a variety of OEM diesel and gasoline engines where there is a need for a 0W-40 grade low SAPS oil.



BASE OIL:  
FULL SYNTHETIC

### SPECIFICATIONS

ACEA C3	MB 229.31
API SN	MB 229.51
API SN Plus	MB 229.52
API SP	MCLAREN MOB 1FS
BENTLEY G 052 930-2B	PORSCHE C40
BENTLEY G 052 930-B2	RENAULT RN 0700
CHRYSLER MS 10725	RENAULT RN 0710
CHRYSLER MS 12633	VW 511 00
FIAT 9.55535-S2	VW G 052 579
GM dexos2™	VW TL 52579
GM dexos™R	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,846
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	67,9
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	13,4
Viscosity Index	ASTM D2270		204
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9,4
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	-
Sulphated ash content	ASTM D874	%	-