



## Carno T HD SAE 10W

### Heavy Duty Engine Oil

This is a high quality mineral heavy duty truck engine oil suitable for naturally aspirated or supercharged diesel and gasoline engines. This product is recommended for fixed diesel engines, and mixed fleets of trucks and cars. The additive technology used in these products ensure long and reliable protection of all the engine parts. These products meet a variety of OEM specifications.



BASE OIL:  
**MINERAL**

#### SPECIFICATIONS

ACEA E2 / E1	MB 228
API CF-4 / SG	MIL MIL-L-2104 E
CATERPILLAR TO-2	MIL MIL-L-46152 E
MAN 270	ZF TE-ML 03B
MB 227	ZF TE-ML 05K

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,875
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	41,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	6,7
Viscosity Index	ASTM D2270		118
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,0
Pour point	ASTM D6892	°C	-24
Flash point	ASTM D92	°C	212
Sulphated ash content	ASTM D874	%	0,70