



P.C.: 790203301

Lexo FA-4 SAE 5W30

Full Synthetic Heavy Duty Engine Oil

This is a full synthetic heavy duty engine oil that improves over 2% fuel economy properties compared to more traditional CJ-4 oils. This product can be used in vehicles that are equipped with turbochargers, superchargers and other after-treatment devices. When this product is used, the engine its energy loss is decreased significantly. This product provides extreme engine protection and has excellent oxidation control and shear stability.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

API FA-4	JASO DL-0-17
CUMMINS CES 20087	MACK EOS-5
DAIMLER TRUCK DTFR 15C130	MB 228.61
DETROIT DIESEL DFS 93K223	RENAULT RLD-5
JASO DH-1-17	VOLVO VDS-5
JASO DH-2-17	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	60,1
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	10,0
Viscosity Index	ASTM D2270		154
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,5
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	216
Sulphated ash content	ASTM D874	%	0,80

All data on this technical data sheet is indicative only

V 202404.01