

PC: 790400201



Joba T SAE 15W40

4-Stroke Motorcycle Engine Oil

This is a motorcycle and scooter engine oil that is made out of the finest mineral base oils. This product is very suitable for (city) touring, racing a cross motors. This product is developed with ester technology additives that ensure that there is optimal friction prevention. This product can be used in vehicles where the API SF/SG /SJ or SL oil is prescribed. With the development of this product, it has been formulated in a way that it offers excellent protection to the gearbox and wet disk clutches. Also, it is very suitable for daily city work-life traffic and the cold start properties ensure optimal engine protection even at cold starts. The JASO MA specification on this product ensures that it can be used in all 4-stroke motorcycle and scooter engines with one oil system for engine, gearbox and wet clutch.



BASE OIL:

MINERAL

SPECIFICATIONS

API SL

JASO MA2

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,880
Kinematic viscosity @ 40 °C	ASTM D445	mm²/s	103,0
Kinematic viscosity @ 100 °C	ASTM D445	mm²/s	13,9
Viscosity Index	ASTM D2270		137
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,0
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	_

All data on this technical data sheet is indicative only