



## Pleto V SAE 15W/50

4-Stroke Motorcycle  
& Scooter Engine Oils

P C : 7 9 0 4 0 0 7 0 1

## Pleto V SAE 15W50

### 4-Stroke Motorcycle Engine Oil

This is an advanced generation of semi-synthetic 4-stroke motorcycle and scooter engine oils. It can be used for both incidental traffic vehicles as well as daily-use vehicles. This product has been based on a formulation that ensures extreme pressure additives in order to maintain the gearbox optimally. It prevents the wet clutches from slipping and the dispersant and detergents that are added ensure optimal cleanliness. This product can be used in city traffic as well as highway traffic and can be used in all types of motorcycles, quads, 4-stroke scooters.



BASE OIL:  
**SEMI-SYNTHETIC**

#### SPECIFICATIONS

API SL

JASO MA2

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,876
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	134,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	17,6
Viscosity Index	ASTM D2270		145
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	7,0
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	237
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01