



Zigo 3P SAE 5W40

Racing Engine Oil

This product can best be used in vehicles that operate under very demanding situations like sports and rally racing. This is a full synthetic engine oil that has been selected out of the best base oils and additives. These base oils naturally contain a high viscosity index. Also high quality European additives were added in order to ensure that this engine oil has excellent resistance against shearing, high resistance against ageing, excellent lubricating film at cold and high temperatures and a very high anti-corrosion and anti-foaming effect.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

ACEA A3 / B3-16	MB 229.3
ACEA A3 / B4	OPEL GM-LL-A-025
API CF	OPEL GM-LL-B-025
API SN	PORSCHE A40
BMW LONGLIFE-01	PSA B71 2296
FIAT 9.55535-H2	RENAULT RN 0700
FIAT 9.55535-M2	RENAULT RN 0710
FIAT 9.55535-Z2	VW 502.00
MB 226.5	VW 505.00

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,848
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	81,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	13,2
Viscosity Index	ASTM D2270		165
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,3
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	238
Sulphated ash content	ASTM D874	%	1,33