



P.C.: 790600901

Pleto GL-4 ZF SAE 80W

Zinc Free Universal Gear Oil

This is a mineral GL-4 manual transmission gear oil that meets the requirements of MB and ZF. This product can be used in manual synchromes gear boxes, transfer boxes and mechanical steering controls. Extreme pressure additives are added to this gear oil in order to extend the transmission lifetime, ensure smooth gear shifting and reduce vibrations. This product has superior quality compared to normal GL-4 gear oils.

BASE OIL:
MINERAL

SPECIFICATIONS

API GL-4	ZF TE-ML 02B
MAN 341 E-1	ZF TE-ML 16A
MAN 341 Z-2	ZF TE-ML 17A
MB 235.1	ZF TE-ML 19C

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,893
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	89,6
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	10,6
Viscosity Index	ASTM D2270		101
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-30
Flash point	ASTM D92	°C	215
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01