



P.C.: 790601001

Pleto GL-4 ZF SAE 75W/80

Zinc Free Universal Gear Oil

This is a full synthetic manual transmission gear oil that can be used for manual transmissions of the modern vehicle fleet. It can be used in syncromesh transmissions. This product ensures smooth gear shifting and prolongs the gearbox lifetime. This gear oil meets a variety of specifications including DAF, Eaton, Volvo, Iveco and Renault. It also includes the Eaton Europe performance standards that include a proven product lifetime of 300.000 km or 3 years. An excellent manual transmission gear oil.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

API GL-4	VOLVO 97307
EATON EXTENDED DRAIN	ZF TE-ML 01L
MAN 341 E-3	ZF TE-ML 02L
MAN 341 Z-4	ZF TE-ML 08
MB 235.4	ZF TE-ML 13
RENAULT B0032 / 2 ANNEX 3	ZF TE-ML 16K
VOLVO 97305	ZF TE-ML 24A

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,860
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	57,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	9,8
Viscosity Index	ASTM D2270		154
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	234
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01