



P.C.: 790601201

## Pleto GL-4 + SAE 75W/90

Universal Gear Oil GL-4 +

This is a full synthetic manual gear oil with the GL-4 + specification. This product significantly improves the gear shifting and ensures easy gear shifting at high temperatures. This product is specifically developed for gearboxes with integrated differentials of front-wheel driven vehicles. This product has an excellent thermal and oxidation stability and significantly extends the transmission life.

BASE OIL:  
**FULL SYNTHETIC**

## SPECIFICATIONS

API GL-4 +	VOLVO 97310
BMW MTF LT-4	VW 501.5
FORD ESD-M2C175	VW G 005 000
FORD ESD-M2C186-A	VW G 005 100
FORD SQM-2C9008-A	VW G 052 145
FORD WSD-M2C200-C	VW G 052 157
FORD WSD-M2C200-D	VW G 052 190
MB 235.72	VW G 052 911
mitsubishi .	VW G 50
OPEL B 040 1043	VW G 51

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,858
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	71,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	14,0
Viscosity Index	ASTM D2270		206
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	200
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01