



P.C.: 790602701

Pleto GO SAE 75W/80

Universal Gear Oil

This is a GL-4 + manual gear oil that can be used for almost all manual gearboxes of passenger car vehicles. This product has been developed in order to reduce the gearbox oil product assortment. This product has been tested on a variety of properties. The result is that it meets the general performance requirements of a very wide portfolio of OEM brands and models. This product can be used all-year round and in all kinds of weather conditions. It ensures smooth shifting and extends transmissions lifetime.



BASE OIL:
MINERAL

SPECIFICATIONS

API GL-4 +	NISSAN 999MP-MTF20P
BMW 83220309031	NISSAN MT-XZ
BMW MTF LT-2	PSA 9730 A2
FIAT 9.55550-MX3	PSA 9730 A8
FIAT 9.55550-MZ1	PSA B71 2330
FORD ESD-M2C186-A	SUBARU K0321-F0090
FORD WSS-M2C200-D2	TOYOTA JWS 227
GM 1940182	VOLVO 97308
GM 1940768	VOLVO 97309
HONDA MTF 94	VOLVO 97310
HYUNDAI 02200-00130 TOD	VW G 052 171
LAND ROVER TYK500030	VW G 052 527
MB 235.1	VW G 052 726
MAZDA MZ312644	VW G 055 538

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,871
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	45,8
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	9,1
Viscosity Index	ASTM D2270		185
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	205
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01