



P.C.: 790700101

Jaxar II-D

Universal ATF Dexron II-D

This ATF II-D is an Automatic Transmission Fluid that is suitable for most passenger cars, forklifts, trucks and buses. It can also be used in power steering systems, torque converters, change gearboxes, fluid clutches and non-complicated hydraulic systems. The high viscosity index offers resistance against foaming and corrosion. This automatic transmission fluid also has a very low pour point ensuring easy shifting at cold starts. NOTE: This ATF II-D is not suitable for automatic transmissions where a Ford M2C33 F/G specification is recommended.



BASE OIL:
MINERAL

SPECIFICATIONS

ALLISON C4	VOITH H55.6335XX
CATERPILLAR TO-2	ZF TE-ML 03D
FORD M2C-138CJ. MERCON	ZF TE-ML 04D
GM 6137-M DEXRON II-D	ZF TE-ML 09
MAN 339 V1 / Z1	ZF TE-ML 11A
MB 236.5	ZF TE-ML 14A
MB 236.7	ZF TE-ML 17C

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	37,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,4
Viscosity Index	ASTM D2270		170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	3,0
Pour point	ASTM D6892	°C	-39
Flash point	ASTM D92	°C	-
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01