



Jaxar III-G

Universal ATF Dexron III-G

This is a semi-synthetic automatic transmission oil. This product can be used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements. This product had a very high viscosity index and is formulated in order to extend the oil lifetime. It ensures excellent low temperature pumpability and extends the transmission lifetime.



BASE OIL:
SEMI-SYNTHETIC

SPECIFICATIONS

ALLISON C4	VOLVO STD 1273.35 (97335)
FORD MERCON	VOLVO STD 1273.37 (97337)
GM 6417-M DEXRON III-G	VOLVO STD 1273.40 (97340)
GM DEXRON II-D	VOLVO STD 1273.41 (97341)
GM DEXRON III-H	ZF TE-ML 03D
MAN 339 V1 / Z1	ZF TE-ML 04D
MB 236.5	ZF TE-ML 05L
MB 236.6	ZF TE-ML 09
MB 236.7	ZF TE-ML 11B
MB 236.8	ZF TE-ML 14A
MB 236.9	ZF TE-ML 17C
VOITH H55.6335XX	ZF TE-ML 21L
VOLVO STD 1273.25 (97325)	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	33,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,1
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	196
Sulphated ash content	ASTM D874	%	-