



Jaxar III-H WHITE

Universal ATF Dexron III-H

This ATF III-H is a high-quality Automatic Transmission Fluid that is developed from the most solvent base oils. This product can be used in automatic gearboxes that require Dexron III-H lubricants. It is also suitable for power steering systems. This ATF III-H has a very high viscosity index and offers resistance against corrosion and foam building. It also has good anti-oxidation and anti-wear properties. The low pour point of this ATF III-H ensures that a good protection is offered also at low temperatures and cold starts.



BASE OIL:
SEMI-SYNTHETIC

SPECIFICATIONS

ALLISON C4	VOITH H55.6335XX
DAIMLER TRUCK DTFR 13C140	VOLVO STD 1273.25 (97325)
DAIMLER TRUCK DTFR 13C150	VOLVO STD 1273.35 (97335)
DAIMLER TRUCK DTFR 13C170	VOLVO STD 1273.37 (97337)
FORD MERCON	VOLVO STD 1273.40 (97340)
GM 6417-M DEXRON III-G	VOLVO STD 1273.41 (97341)
GM DEXRON II-D	ZF TE-ML 03D
GM DEXRON III-H	ZF TE-ML 04D
MAN 339 V1/Z1	ZF TE-ML 05L
MB 236.5	ZF TE-ML 09
MB 236.6	ZF TE-ML 11B
MB 236.7	ZF TE-ML 14A
MB 236.8	ZF TE-ML 17C
MB 236.9	ZF TE-ML 21L

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,847
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	33,9
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,1
Viscosity Index	ASTM D2270		179
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	196
Sulphated ash content	ASTM D874	%	-