



P C : 7 9 0 7 0 0 5 0 1

Jaxar IV

Universal ATF Dexron IV

This is a full synthetic automatic transmission fluid for universal applications. This product has a wide range of specifications and can be used in vehicles of a wide range of OEM. This product can be used in the latest generation of automatic transmissions and torque converters for most passenger cars, small vans and small buses. This product is formulated in order to ensure smooth gear shifting.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

AISIN-WARNER AW-1	GM DEXRON HP
AISIN-WARNER AW-2	GM DEXRON VI
AISIN-WARNER JWS 3324	HONDA DW-1
ALLISON C4	HYUNDAI NWS-9638 T5
BMW 83222152426	HYUNDAI SP-IV
BMW 83222167718	HYUNDAI SPH-IV
BMW 83 22 0 397 114	ISUZU WSI
BMW 83 22 2 305 397	JAGUAR 02JDE26444
BMW 83 22 9 407 858	LAND ROVER LR023288
BMW ATF 3	MAZDA FZ
BMW L 12108	MB 236.12
BMW M-1375.4	MB 236.41
CHRYSLER 68157995AA	MITSUBISHI ATF J3
FIAT 9.55550-AV2	NISSAN MATIC-S
FIAT 9.55550-AV5	TESLA ATF9 / EDF2
FORD MERCON LV	TOYOTA AUTO FLUID WS
FORD MERCON SP	VW G 055 005
FORD WSS-M2C195-A	VW G 055 162
FORD WSS-M2C924-A	VW G 055 540
FORD WSS-M2C938-A	VW G 060 162

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,852
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	29,4
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	6,1
Viscosity Index	ASTM D2270		162
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	210
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01