



P.C.: 790700701

Jaxar VI

Universal ATF Dexron VI

This ATF VI is an all-round low viscosity Automatic Transmission Fluid. It is developed particularly for automatic transmissions that require low viscosity automatic transmission fluids. This ATF VI ensures easy shifting under all operating temperatures and can be used in a wide temperature range because of its low pour point. Also, this ATF VI easily meets prescribed intervals because of its excellent oxidation and thermal stability. This product cannot be used in DTC's and CVT's or when an oil with Ford Type F/G is prescribed.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

GM DEXRON VI**VOITH H55.6335XX****MB 236.41**

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,855
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	30,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	6,0
Viscosity Index	ASTM D2270		151
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-45
Flash point	ASTM D92	°C	-
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01