



P.C.: 790701201

## Jaxar MB 236.17

ATF 9 Speed MB 236.17

This is a full synthetic Automatic Transmission Fluid that contains a very low viscosity and high viscosity index. This product has been specifically developed for the Mercedes-Benz 9 speed automatic transmissions. This product ensures significant fuel saving properties and is applicable in automatic transmissions where the MB 236.17 specification is prescribed. This product can be used in the newest 9G-tronic automatic transmissions of the series W9A 700 / NAG3 types. This product is backwards compatible with MB 236.16.



BASE OIL:  
**FULL SYNTHETIC**

### SPECIFICATIONS

**MB 236.17**

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,845
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	-
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	4,8
Viscosity Index	ASTM D2270		166
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-54
Flash point	ASTM D92	°C	-
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01