



P C : 7 9 0 7 0 1 3 0 1

Jaxar ZF 6

ATF ZF 6 Speed Transmissions

This is a full synthetic automatic transmission fluid that has been specifically developed for the ZF 6 speed automatic transmissions. They are mainly intended for the ZF 6 speed transmissions for the BMW group, Jaguar and Land Rover, but it can also be used in a variety of another OEM. This product ensures a good protection in the automatic gearbox and ensures smooth shifting. It significantly increases the lifetime of the transmission.

BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

AML 4G4319A509 / AA / S

HYUNDAI 040000C90SG

BENTLEY PY112995PA

JAGUAR FLUID 8432

BMW 83220142516

LAND ROVER TYK500050

BMW 83 22 2 305 396

MASERATI 231603

BMW ATF 2

VW G 055 005

BMW M-1375.4

ZF TE-ML 11

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,845
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	31,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	6,2
Viscosity Index	ASTM D2270		153
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	202
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01