



P C : 7 9 0 7 0 1 4 0 1

Jaxar ZF 8

ATF ZF 8 Speed Transmissions

This is a full synthetic automatic transmission fluid that is developed for ZF 8HP automatic transmissions. This product can also be used in automatic transmissions with 8HP45, 8HP55, 8HP70 and 8HP90. This automatic transmission fluid has a superior protection and extends oil and automatic transmission life. It has excellent cold start properties, and contributes to fuel saving.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

BMW 83222152426

JAGUAR 02JDE26444

BMW 83 22 2 289 720

LAND ROVER LR023288

BMW ATF3+

VW G 060 162

CHRYSLER 68157995AA

ZF TE-ML 11

FIAT 9.55550-AV5

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,852
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	28,1
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	5,9
Viscosity Index	ASTM D2270		164
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	210
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01