



Jaxar DCT

Double Clutch Transmission Fluid

This is a full synthetic automatic transmission oil that has been developed for transmission with dual clutch transmissions (DCT). The dual clutch has initially been developed for racing and is based on the fact that the transmission has two clutches. One clutch is for the even gears, and the other for the uneven gears. This product is specifically formulated for this type of transmissions. Because the transmission does not shift between gears but between clutches, extreme pressure performance and friction prevention properties are needed. This product is developed in a way that even under extreme pressure conditions, this product does not lose its quality. It ensures trouble-free operation of DCT gearboxes. This product can be used for Direct shift Gearboxes (DSG) of the VAG group, as well as other 6-speed DCT transmissions, such as Ford Powershift, Chrysler Powershift, Volvo Powershift, Mitsubishi TC-SST, BMW Drivelogic 7-speed, etc. This product is NOT intended for VW dry clutch DSG type 0AM, 02M, 02Q and 02S.



BASE OIL:
FULL SYNTHETIC

SPECIFICATIONS

BMW 83220397244	NISSAN DCT FLUID
BMW 83222409710	NISSAN GT-R R35
BMW 83222433157	NISSAN R35 SPECIAL
BMW DCTF-1	PORSCHE 000.043.20
BMW DCTF-2	PORSCHE 000.043.207.29
BMW DTF 1	PORSCHE 000.043.207.30
BMW FFL-4	PORSCHE 999.917.080.01
BMW MTF LT-3	PORSCHE TF 0870
BMW MTF LT-5	PSA 9730 A8
CHRYSLER 68044345EA	PSA 9734 S2
FERRARI TF DCT-F3	RENAULT BOT450 EDC 6-SPEED
FIAT 9.55550-DA11	RENAULT DC4
FIAT 9.55550-MZ2	RENAULT DW5
FIAT 9.55550-MZ6	TOYOTA JWS 2271
FORD F-DC	TOYOTA LF
FORD WSS-M2C200-D2	VOLVO 1161839
FORD WSS-M2C200-D3	VOLVO BOT341 #1161838
FORD WSS-M2C200-E1	VW G 052 171
FORD WSS-M2C218-A1	VW G 052 182
FORD WSS-M2C936-A	VW G 052 512
GM FFL-4	VW G 052 513
HONDA MTF III	VW G 052 527
MB 236.21	VW G 052 529
MB 236.24	VW G 052 726
MB 236.25	VW G 052 798
MB 239.21	VW G 055 529
MB SLS A0019898603	VW G 055 549
MCLAREN FFL-4	VW G 060 726
MITSUBISHI DIAMOND QUEEN	VW G 070 726
SSTF-1	VW TL 52 182
NISSAN 999MP-6TRT00P	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,869
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	38,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,5
Viscosity Index	ASTM D2270		170
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-50
Flash point	ASTM D92	°C	198
Sulphated ash content	ASTM D874	%	-