



P.C.: 790701801

Jaxar A/A

ATF Specials A/A

This is a very in depth formulated automatic transmission fluid that is based on solvent-refined oils. This product can only be used in automatic and semi-automatic gearboxes, power steering where ATF Type A Suffix A oil is prescribed. The high viscosity index and low pour point of this product ensure optimal performance in a very broad temperature range.



BASE OIL:
MINERAL

SPECIFICATIONS

DAIMLER TRUCK DTFR 13C120	GM 6137-M DEXRON II-D
FORD ESP-M2C138-CJ	GM DEXRON TYPE A. SUFFIX A
FORD MERCON	MB 236.2
GM 6032-M DEXRON	

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	-
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	36,7
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	7,1
Viscosity Index	ASTM D2270		161
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	1,5
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	198
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01