



P.C.: 791100201

Noto STOU SAE 10W/40

STOU Agriculture Performance Oil

This is a semi-synthetic Universal Super Tractor Transmission Oil that is used in engines, transmissions, wet brakes and hydraulic systems of vehicles used in the agriculture/off highway segment. This product has been developed to perform very well also in colder temperature environments. It ensures instant lubrication at usage and reduces risk of wear. This product can be used for lubricating charged and uncharged diesel engines. It can also be used in 4-stroke gasoline engines and LPG engines. In addition to that it provides excellent properties for the gearbox, differential, final drive, power take-off, wet brakes and hydraulic systems.



BASE OIL:
SEMI-SYNTHETIC

SPECIFICATIONS

ACEA E3	MF M 1135
ALLISON C4 (AGRICULTURE APPLIC.)	MF M 1139
API CG-4	MF M 1143
API GL-4	MF M 1144
API GL-5 (LOW SPEED / HIGH TORQUE)	MF M 1145
API SF / CE	NH NH 024C
CASE MAT 3525	NH NH 410B
CASE MAT 3526	NH NH 420A
DIN 51524 T3 HVLPD	ZF TE-ML 03A
FORD ESN-M2C134 C / D	ZF TE-ML 05K
FORD ESN-M2C159 B / C	ZF TE-ML 06A
FORD FNH 82009203	ZF TE-ML 06B
JD J20C	ZF TE-ML 06C
JD J27	ZF TE-ML 07B
	ZF TE-ML 07D

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,875
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	96,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	14,1
Viscosity Index	ASTM D2270		150
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-36
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01