



P.C: 791100301

Noto STOU SAE 15W/30

STOU Agriculture Performance Oil

This is a Universal Super Tractor Transmission Oil that is used in engines, transmissions, wet brakes and hydraulic systems of vehicles used in the agriculture/off highway segment. This product has been developed to perform very well also in colder temperature environments. It ensures instant lubrication at usage and reduces risk of wear. This product can be used for lubricating charged and uncharged diesel engines. It can also be used in 4-stroke gasoline engines and LPG engines. In addition to that it provides excellent properties for the gearbox, differential, final drive, power take-off, wet brakes and hydraulic systems.



BASE OIL:
MINERAL

SPECIFICATIONS

ACEA E3	JD J20C
AFNOR NF E 68-603 E	JD J27
ALLISON C4 (AGRICULTURE APPLIC.)	MF M 1135
API CG-4	MF M 1139
API GL-4	MF M 1143
API GL-5 (LOW SPEED / HIGH TORQUE)	MF M 1144
API SF / CE	MF M 1145
CASE MAT 3525	NH NH 030C
CASE MAT 3526	ZF TE-ML 03A
DIN 51524 T3 HVLPD	ZF TE-ML 05K
EATON VICKERS M-2950-S	ZF TE-ML 06A
FORD ESN-M2C134 C / D	ZF TE-ML 06B
FORD ESN-M2C159 B / C	ZF TE-ML 06C
FORD FNH 82009202	ZF TE-ML 07B
	ZF TE-ML 07D

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,874
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	81,7
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	10,8
Viscosity Index	ASTM D2270		118
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,7
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	222
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01