



P.C.: 791101001

Macro UTTO 400

Universal Tractor Transmission Oil

This is a Universal Tractor Transmission Oil that is used in transmissions, hydraulic lifts, rear axles, wet brakes of agriculture equipment, offroad equipment and mobile hydraulic systems like cranes, junction box and power steering. This product is not suitable for lubricating the engine. It provides complete system protection and increases equipment lifetime.



BASE OIL:
MINERAL

SPECIFICATIONS

ALLIS CHALMERS PF-821

ALLISON C3 / C4

API GL-4

CASE MS1205

CASE MS1206

FORD ESN-M2C-134 A / B

FORD ESN-M2C-86 A / B

MF M 1135

NH NH 420A

RENAULT THFI

ZF 05E

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,888
Kinematic viscosity @ 40 °C	ASTM D445	mm ² /s	90,0
Kinematic viscosity @ 100 °C	ASTM D445	mm ² /s	10,9
Viscosity Index	ASTM D2270		106
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	6,9
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	220
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01