



P.C.: 791101501

## Kentros 4S MCH SAE 10W/40

4-Stroke Agriculture Performance Oil

This is a semi-synthetic engine oil suitable for off-road equipment: motors, mechanical transmissions, transaxles, hydraulic systems, wet brakes and compressors. This product ensures optimal system cleanliness and prolongs equipment lifetime. This product meets specifications of many manufacturers and is a perfect product for the whole agriculture fleet



BASE OIL:  
SEMI-SYNTHETIC

### SPECIFICATIONS

ACEA E3	FORD FNH 82009203
ALLISON C4 (AGRICULTURE APPLIC.)	JD J20C
API CG-4	JD J27
API GL-4	MF M 1144
API GL-5 (LOW SPEED / HIGH TORQUE)	MF M 1145
API SF / CE	NH NH 024C
CASE MAT 3525	NH NH 410B
CASE MAT 3526	NH NH 420A
CATERPILLAR TO-2	ZF TE-ML 03A
DIN 51524 T3 HVLPD	ZF TE-ML 05K
EATON VICKERS I-280-S	ZF TE-ML 06A
EATON VICKERS M-2950-S	ZF TE-ML 06B
FORD ESN-M2C134 C / D	ZF TE-ML 06C
FORD ESN-M2C159 B / C	ZF TE-ML 07B
	ZF TE-ML 07D

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,873
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	94,0
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	14,1
Viscosity Index	ASTM D2270		154
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	10,4
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	225
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202404.01