



P.C.: 795600401

## Maryn 2T TCW3 SS

### 2-Stroke Outboard Engine Oil

This is a semi-synthetic outboard engine oil suitable for water-cooled 2-stroke outboard engines meeting NMMA TC-W3 specifications. The semi-synthetic composition of this oil ensures that the engine lifetime is extended tremendously. The ash less components in this prevents the formation of deposits, pre-ignition and spark plug fouling. This product can be used for 2-stroke gasoline engines with high power like; outboard motors, jet skis and personal watercraft.

BASE OIL:  
**SEMI-SYNTHETIC**

#### SPECIFICATIONS

API TC

NMMA TC-W3

JASO FC

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,859
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	42,7
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	7,8
Viscosity Index	ASTM D2270		155
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	5,2
Pour point	ASTM D6892	°C	-42
Flash point	ASTM D92	°C	100
Sulphated ash content	ASTM D874	%	0,00

All data on this technical data sheet is indicative only

V 202404.01