



P.C.: 795600501

## Maryn BIO 2T

### Biodegradable 2-Stroke Outboard Engine Oil

This is a full synthetic, biodegradable outboard engine oil developed for water-cooled 2-stroke gasoline engines. This product is also suitable for air-cooled engines. This product is developed for equipment where the tank is filled with a mixture of gasoline and oil, and for those with separate oil reservoirs. This product is biodegradable, and ensures a long lifetime of the 2-stroke engine. This product can be used for all water-cooled 2-stroke gasoline engines with a dilution level of 2% (1 in 50) and 1% (1 in 100). It is suitable for outboard engines, water skis and personal watercraft.

BASE OIL:  
**FULL SYNTHETIC**

#### SPECIFICATIONS

**API TC+****CEC L-33-A-93****NMMA TC-W3**

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,895
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	49,9
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	10,0
Viscosity Index	ASTM D2270		166
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	5,6
Pour point	ASTM D6892	°C	-33
Flash point	ASTM D92	°C	102
Sulphated ash content	ASTM D874	%	0,00

All data on this technical data sheet is indicative only

V 202404.01