



# Mimus FT SAE 10W

Fork Oils

## Mimus FT SAE 10W

### Fork Oil

This is a fork oil that has a very high viscosity index. It has been based on mineral base oils and will provide optimum dampening control in a very wide temperature range. This product can be used for vehicles on road and off road. The quick air release, low foaming properties and excellent elastomer compatibility ensure that this product has an excellent effect on equipment maintenance and performance. This fork oil is very universal of use and can be used in telescopic forks, upside-down forks and dampers of bikes, scooters, mopeds and other two-wheel driven vehicles.

BASE OIL:  
**MINERAL**

### SPECIFICATIONS

**DIN 51524 PART 3**

GRADE	METHOD	UNIT	VALUE
Density	ASTM D4052	kg/l	0,874
Kinematic viscosity @ 40 °C	ASTM D445	mm <sup>2</sup> /s	31,5
Kinematic viscosity @ 100 °C	ASTM D445	mm <sup>2</sup> /s	6,3
Viscosity Index	ASTM D2270		155
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	-
Pour point	ASTM D6892	°C	-48
Flash point	ASTM D92	°C	176
Sulphated ash content	ASTM D874	%	-

All data on this technical data sheet is indicative only

V 202412.01